

Molift Mover 300

When a high safe working load is needed.



Description

Molift Mover 300 excl. suspension Standard 15050 With Support arms 15150

Material

Aluminium, steel

Service Software

Included

Total weight

Regular: 39.3 kg (90 lbs) With support arms: 45.9 kg (101.2 lbs)

Length

1285 mm (50,6")

Width chassis/legs outer

690 mm (27,2")

Width open legs inner

1065 mm (41,9")

Hoisting height

375 - 1775 mm (14,8 - 69,9")

Hoisting interval

1400 mm (55,1")

Leg height

115 mm (4,5")

Battery

NiMh 26.4 V - 2.2 Ah Item no. 1341000

Battery charge time

Ca 3 hours

Hoisting speed

2.7 cm/ sec (1.1"/ sec)

Rated performance

50 hoists at: 75 kg and 50 cm (165 lbs and 19.7")

Cleaning instructions

Use pH-neutral cleaning agents. If disinfection is required, use isopropyl alcohol. Do not use abrasive or corrosive substances for cleaning.





Features



Unique patented Quick release Molift Mover 300 has a standard 4-point suspension with a Quick release function which provides options of other suspensions in different dimensions.



Many options
Molift Mover 300 can
be used with a 4-point
suspension. They are avalibale
in two variants and can be
interchanged easily without
tools.



High safe working load Molift Mover 300 has a safe working load of 300 kg (660 lbs) and still weighs only 39.3 kg (90 lbs).



Weight scale
The Molift Mover 300 scale
is approved Class III and
complies with all technical
standards. It can also calculate
BMI (Body Mass Index) with a
simple touch.



Toll Free: 1-800-442-2246